







PIPE DIAMETER UP TO DN 100 À DN 2500 MM



SALES DESCRIPTION

· Set of 2 probes with their support

External probes for liquid flow measurement on a full pipe.
 Standard applications - clear liquids and pipes
 Mounting on a pipe from DN100 to DN2500

Maximum operating temperature of 80°C
Push-Pull connection
Magnetic support in 2 parts SU-1735 included

INSTALLATION

APPLICATION

CONDITIONS OF USE

DIAMETER OF THE PIPE (IN MM)

THICKNESS OF THE PIPE

CONNECTIC

MOUNTING TYPE

TEMPERATURE IN °C

COMPATIBLE CONVERTERS

ATEX

ΙP

PROBES USED

SUPPORT TYPE

MATERIAL OF THE PROBES

MATERIAL OF THE SUPPORT

SIZE (IN MM)

WFIGHT

FREQUENCY (IN HZ)

Non intrusive

Full pipe

Standard - clear liquids and pipes

100 - 2500

> 1 mm

Push Pull

/VNW

From -20 °C to +80°C

ALL

NO

Type IP67

SE-1595/BT/05

SU-1735 - Magnetic fixation

Plexiglass

Anodized aluminum

500 x 48 x 66,2 (Can be split in 2 parts)

1390 g

500 kHz

NON CONTRACTUAL DOCUMENT

