

Uf 801P

ULTRASONIC PORTABLE FLOW METER



MEDIA
MEASURED
LIQUIDS
& GASES



PIPE DIAMETERS
UP TO
10000MM



MODEL
STANDARD
DUAL PIPE
DUAL CHORD
CALORIMETER
DUAL CALORIMETER

COMPACT

- > Light weight (less than 1kg)
- > Easy to use

ADVANCED FUNCTIONS

- > Multi-parameter data logger
- > Stores up to 11 configurations/sites
- > Timer/programmer
- > Optional Input/output modules (analogue, digital)

HIGH PERFORMANCE

- > Graphic screen
- > Echo, gain and quality index displayed
- > Battery life up to two months, using timed operation

RELIABLE

- > Automatic zero calibration
- > Ten flow calculations per second

ROBUST

- > IP68 ABS enclosure

MULTIPLE USES

- > On every type of homogeneous liquid, even non-conductive
- > On most types of gases - high and medium pressure*
- > Non ideal flow conditions taken into account



TYPICAL APPLICATIONS

Drinking water:
Leakage detection, pump flow control, control of in-line flow meters

Water (raw, waste):
Pump flow control

Flow surveys:
Troubleshooting installations, resolving disputes

Civil engineering:
Validation of system performance before handover of a project

Climate engineering:
System balancing, thermal assessment

Hydrocarbons:
Temporary flow measurement

* APPLICATION CONDITIONS: PLEASE CONTACT US

Ultraflux



EXPERT IN FLOW METERS
SINCE 1974

Uf801P

MODEL	STANDARD	DUAL PIPE	DUAL CHORD	CALORIMETER	DUAL CALORIMETER
NATURE OF EQUIPMENT	Portable				
INTERNAL Ø OF PIPE	From 8mm to 9,900mm approximately (depending on wall thickness)				
EXTERNAL Ø OF PIPE	From 10mm to 10,000mm				
STANDARD MOUNTED INPUTS/OUTPUTS	—				
LT CONFIGURATION - DUAL MODULE -	—			PT100/PT1000 2-input module taking up the physical space of two modules	
SUPPLEMENTARY LT CONFIGURATION (DUAL CALORIMETRY) - DUAL MODULE -	—	—	—	—	PT100/PT1000 2-input module taking up the physical space of two modules
USE	Flow measurement	Flow measurement in two pipes (with one speed chord per pipe)	Flow measurement with two speed chords	Flow measurement and calorimetry	Flow measurements in two pipes and dual calorimetry
SINGLE OR DUAL PIPE	Single pipe	Dual pipe	Single pipe	Single pipe	Dual pipe
SINGLE OR DUAL CHORD	Single chord	Single chord	Dual chord	Single chord	Single chord
PIPE THICKNESS MEASUREMENT	Function available in digital and graphical mode(SE-1701)				
IN OPTION, SINGLE INPUT/OUTPUT MODULES	Up to 4 modules to choose from: > 1 isolated, active analogue output: current 4-20mA, 0-20mA, 0-24mA · Module 1 > 2 static relay outputs usable as frequency outputs (up to 1kHz) · Module 2 > 2 isolated current inputs 4-20mA, 0-20mA, 0-24mA · Module 3 > 2 0-10V voltage inputs · Module 4 > 2 contact inputs (pulse or state) · Module 6			Up to 2 modules to choose from:	—
DISPLAY	Numeric and graphic (14 lines x 20 characters) · Backlit LCD screen with time delay feature				
TROUBLESHOOTING HELP	Oscilloscope function (echo displayed) · Gain · Quality index				
SET-UP	> Quick and simple - uses 7-key touch pad with 2 for dynamic allocation - or via dedicated software supplied > Possible to build in an access code				
INFORMATION STORAGE	> 4MB data logger: time stamping - between 1 and 30 variables - up to 266,706 lines > 3-variable time stamping: 133,353 lines · 14 variables: 35,560 lines · 30 variables: 17,206 lines > Logging frequency from 1 second to 24 hours				
OPERATING SYSTEM	Windows for transfer of content and operation of logger using common software (Excel, etc.)				
PROGRAMMER	Programmable power-up to increase the logger's battery life				
2/3 LANGUAGES	English & Russian or French & English + 1 additional language to be chosen: German · Portuguese · Spanish · Italian				
BATTERY LIFE	Up to 14hr continuous use · Charge indicator				
SERIAL LINK	RS232 to JBUS/MODBUS protocol · 115,200 Bauds · 1 RS232 to USB converter link cable included				
ACCESSORY INCLUDED	1 RS232 to USB converter link cable				
ELECTRICAL CHARACTERISTICS	> 12V NiMh sealed battery > Charger with input: 100-240V ac / 1.05-0.55A / 47-63Hz and output: 18V / 2.5A" > Cable for auxiliary power supply available as an option				
ENCLOSURE	ABS · 900g · 220 x 115 x 64mm				
PROTECTION	IP68				
TEMPERATURE RANGE	For use from -10°C to 50°C				

TECHNOLOGY	PERFORMANCES			
ULTRASONIC TRANSIT TIME > Continuous bidirectional measurement SIGNAL ANALYSIS > By Digital Signal Process (real-time Echo Shape Control, digital filtering and regulation of gain on each firing)	ACCURACY > Up to 0.5% REPEATABILITY > Up to 0.1% LINEARITY > Up to 0.1%	TEMPORAL RESOLUTION > 0.1ns TIME BETWEEN EACH FLOW CALCULATION > 100ms UNITS OF MEASUREMENT > From litres per second to cubic metres per day	VOLUME METERING > From a millilitre up to 1,000 cubic metres MULTI-LAYER PIPE > Up to three materials taken into consideration MEMORY CAPACITY > Up to 11 configurations	OTHER IMPORTANT INFORMATION > Laminar and turbulent transitions considered (calculation of the Reynolds number) - except for parallel chords > Freedom to mount probes: modes /, V, N and W